

FEATURES


- Flexible, can be bent into shape for easy installation
- 310 stainless steel sheath for resistance to corrosion and oxidation

M8 x 1.0 mm fine pitch threaded pot seal

 Wide temperature range of -100 to +1100°C

RS PRO Type K Thermocouple 300mm Length, 3mm Diameter \rightarrow +1100°C

RS Stock No.:219-4539



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

These thermocouple temperature probes have durable construction with a 310 stainless steel mineral insulated flexible probe sheath that can be bent and formed to suit a wide range of applications. The thermocouple has a single element insulated hot junction for a reduction in electrical interference and a M8 x 1.00 mm fine pitch threaded pot seal with a temperature rating of $200^{\circ}C$

General Specifications

Thermocouple Type	Туре К
Temperature Measurement Range	-100 to +1100°C
Construction	These thermocouple temperature probes have durable construction with a 310 stainless steel mineral insulated flexible probe sheath that can be bent
Measuring Junction	Underground
Application	heat exchangers, power stations, brick and cement kilns, heat treatment and annealing furnaces, thermostats, food thermometers, vehicle diagnostics and in laboratories

Mechanical Specifications


Probe Diameter	3mm
Probe Length	300mm
Probe Body Material	Stainless Steel
Insulation / Sheath Material	310SS
Termination Type	Cable
Cable Insulation	Teflon Insulated

Approvals

Standards Met

IEC





T/C Type	Conductors	Length	Termination	+Positive tail wire	-Negative tail wire code	Allied Code	RS order Code
'K'	1/0.2mm	1 metre	Mini plug	Green	White	70643600	363-0250
'K'	1/0.2mm	2 metre	Mini plug	Green	White		110-4482
'K'	1/0.2mm	5 metre	Mini plug	Green	White		123-6306
'K'	1/0.2mm	10 metre	Mini plug	Green	White		123-6307
1' 1' 1'	1/0.2mm 1/0.2mm 1/0.2mm 1/0.2mm	1 metre 2 metre 5 metre 10 metre	Mini plug Mini plug Mini plug Mini plug	Black Black Black Black	White White White White	70643599	363-0244 123-6308 123-6309 123-6310
'T'	1/0.2mm	1 metre	Mini plug	Brown	White	70643601	363-0266
'T'	1/0.2mm	2 metre	Mini plug	Brown	White		123-6311
'T'	1/0.2mm	5 metre	Mini plug	Brown	White		123-6312
'T'	1/0.2mm	10 metre	Mini plug	Brown	White		123-6313

Thermocouples



	Conductors	Cores	Jacket	Reel Length	Allied	RS order code
Exten	sion:					
KX	7/0.2mm	+Green/-White	Green	10 metres	70657084	827-5615
KX	7/0.2mm	+Green/-White	Green	25 metres	70641729	236-3820
KX	7/0.2mm	+Green/-White	Green	50 metres	70657085	827-5619
KX	7/0.2mm	+Green/-White	Green	100 metres	70646156	611-7889
КХ	7/0.2mm	+Green/-White	Green	200 metres	70657088	827-5628
	- 10 - 0					
JX	7/0.2mm	+Black/-White	Black	10 metres	70641640	219-4753
XL	7/0.2mm	+Black/-White	Black	25 metres	70657078	827-5592
JX	7/0.2mm	+Black/-White	Black	50 metres	70657079	827-5596
JX	7/0.2mm	+Black/-White	Black	100 metres	70641737	236-3915
XL	7/0.2mm	+Black/-White	Black	200 metres	70657081	827-5606
тх	7/0.2mm	+Brown/-White	Brown	10 metres	70641637	219-4703
TX	7/0.2mm			25 metres		236-3870
	7/0.2mm	+Brown/-White	Brown		70641734	
TX	7/0.2mm	+Brown/-White	Brown	50 metres	70657095	827-5653
тх	7/0.2mm	+Brown/-White	Brown	100 metres	70651749	762-1146
тх	7/0.2mm	+Brown/-White	Brown	200 metres	70657098	827-5662
NX	7/0.2mm	+Pink/-White	Pink	10 metres	70641635	219-4668
NX	7/0.2mm	+Pink/-White	Pink	25 metres	70657091	827-5637
NX	7/0.2mm	+Pink/-White	Pink	50 metres	70657089	827-5631
NX	7/0.2mm	+Pink/-White	Pink	100 metres	70657092	827-5640

Т/С Туре	Conductors	Cores	Reel Length	Allied code	RS order code
J	1/0.2mm	+Black/-White	25 metres	70657194	827-5980
J	1/0.2mm	+Black/-White	50 metres	70657195	827-5984
J	1/0.315mm	+Black/-White	25 metres	70657198	827-5993
J	1/0.315mm	+Black/-White	50 metres	70657199	827-5996
к	1/0.315mm	+Green/-White	25 metres	70657200	827-6000
к	1/0.315mm	+Green/-White	50 metres	70657205	827-6019
т	1/0.315mm	+Brown/-White	25 metres	70657208	827-6028
т	1/0.315mm	+Brown/-White	50 metres	70657206	827-6022
J	1/0.508mm	+Black/-White	25 metres	70657197	827-5990
J	1/0.508mm	+Black/-White	50 metres	70657201	827-6003
к	1/0.508mm	+Green/-White	25 metres	70657203	827-6012
к	1/0.508mm	+Green/-White	50 metres	70657204	827-6016
J	7/0.2mm	+Black/-White	25 metres	70657202	827-6006
к	7/0.2mm	+Green/-White	25 metres	70657207	827-6025
т	7/0.2mm	+Brown/-White	25 metres	70657209	827-6031
Ν	7/0.2mm	+Pink/-White	25 metres	70657210	827-6034



Т/С Туре	Conductors	Cores	Reel Length	Allied code	RS order code
КХ	1/0.2mm	+Yellow/-Red	25 metres	70656106	814-0030
КХ	1/0.2mm	+Yellow/-Red	50 metres	70656111	814-0049
КХ	1/0.2mm	+Yellow/-Red	100 metres	70656109	814-0042
KX	7/0.2mm	+Yellow/-Red	25 metres	70656110	814-0046
KX	7/0.2mm	+Yellow/-Red	50 metres	70656113	814-0055
KX	7/0.2mm	+Yellow/-Red	100 metres	70656114	814-0058
KX	1/0.3mm	+Yellow/-Red	25 metres	70656104	814-0024
KX	1/0.3mm	+Yellow/-Red	50 metres	70656107	814-0033
KX	1/0.3mm	+Yellow/-Red	100 metres	70656108	814-0036
TX	1/0.3mm	+Blue/-Red	25 metres	70656121	814-0080
TX	1/0.3mm	+Blue/-Red	50 metres	70656126	814-0099
TX	1/0.3mm	+Blue/-Red	100 metres	70656124	814-0092
TX	1/0.2mm	+Blue/-Red	25 metres	70656125	814-0096
TX	1/0.2mm	+Blue/-Red	50 metres	70656128	814-0106
TX	1/0.2mm	+Blue/-Red	100 metres	70656129	814-0109

Т/С Туре	Conductors	Cores	Jacket	Reel Length	Allied code	RS order code			
Extension:									
KX	7/0.2mm	+Yellow/-Red	Yellow	25 m	70656102	814-0018			
KX	7/0.2mm	+Yellow/-Red	Yellow	100 m	70656105	814-0027			
кх	7/0.2mm	+Yellow/-Red	Yellow	200 m	70656103	814-0020			
JX	7/0.2mm	+ White/-Red	Black	25 m	70656096	813-9995			
XL	7/0.2mm	+ White/-Red	Black	100 m	70656098	814-0005			
JX	7/0.2mm	+ White/-Red	Black	200 m	70656099	814-0008			
тх	7/0.2mm	+Blue/-Red	Blue	25 m	70656119	814-0074			
тх	7/0.2mm	+Blue/-Red	Blue	100 m	70656122	814-0083			
ТХ	7/0.2mm	+Blue/-Red	Blue	200 m	70656123	814-0086			
Compensating:									
VX (KCB)	7/0.2mm	+Yellow/-Red	Yellow	25 m	70656127	814-0103			
VX (KCB)	7/0.2mm	+Yellow/-Red	Yellow	100 m	70656130	814-0112			
VX (KCB)	7/0.2mm	+Yellow/-Red	Yellow	200 m	70656131	814-0115			

Thermocouples



	Conductors	Cores	Jacket	Reel Length	Allied Code	RS order code
Compensating:						
VX (KCB)	7/0.2mm	+Green/-White	Green	10 metres	70657082	827-5609
VX (KCB)	7/0.2mm	+Green/-White	Green	25 metres	70641629	219-4551
VX (KCB)	7/0.2mm	+Green/-White	Green	50 metres	70657080	827-5603
VX (KCB)	7/0.2mm	+Green/-White	Green	100 metres	70641630	219-4573
VX (KCB)	7/0.2mm	+Green/-White	Green	200 metres	70657083	827-5612
VX (KCB)	13/0.2mm	+Green/-White	Green	10 metres	70657086	827-5621
VX (KCB)	13/0.2mm	+Green/-White	Green	25 metres	70657087	827-5625
VX (KCB)	13/0.2mm	+Green/-White	Green	50 metres	70657090	827-5634
VX (KCB)	13/0.2mm	+Green/-White	Green	100 metres	70651750	762-1152
U (RCA)	7/0.2mm	+Orange/-White	Orange	10 metres	70657096	827-5656
U (RCA)	7/0.2mm	+Orange/-White	Orange	25 metres	70646158	611-7902
U (RCA)	7/0.2mm	+Orange/-White	Orange	50 metres	70657097	827-5659
		-	-			
U (RCA)	13/0.2mm	+Orange/-White	Orange	10 metres	70641641	219-4769
U (RCA)	13/0.2mm	+Orange/-White	Orange	25 metres	70657093	827-5643
U (RCA)	13/0.2mm	+Orange/-White	Orange	50 metres	70657094	827-5647