

**HB 4807 ( 3M 969 )**

## FEATURES

**HB 4807**

Roll dimensions: 12mm x 33m

This tape is a double-sided tissue tape 150 micron thick coated with a solvent acrylic pressure sensitive adhesive, giving very good high and low temperature resistance. The tape has a reverse wound format with the exposed adhesive tape on the outside of the roll configured for use with an ATG applicator tape gun. The tape is wound on special ATG cores for use with the applicator.

**Applications:**

Used in the printing industry for design mock-ups, used for light fabrication using thin plastics and card. Point of sale and advertising. Exhibition temporary signage. Mounting of posters and displays.

# RS PRO ATG Tape High Tack Adhesive

RS Stock No: 224-3438



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

**Product description :** This tape is a reverse wound acrylic double-sided tissue tape  
Designed for use in an ATG tape applicator gun. Produced on a core designed to be compatible for ATG applications.

**Construction :** 12 micron thick paper tissue is coated each side with a solvent acrylic pressure sensitive adhesive 69 micron thick each side.  
White paper liner 120 micron thick reverse wound exposing the adhesive

This tape has a shelf life of 1 year when store at an ambient temperature of 15 – 25 °C

## General Specifications

Item	Unit	Spec.	Test method
Base Carrier Thickness	µm	12	ASTM D3652
Tape Total thickness	µm	150	ASTM D3652
Peel Strength	N/m	700	ASTM D3330
Tensile Strength	N/m	1000	ASTM D3759
Elongation at break	%	4	ASTM D3759
Temperature Resistance	-	-40 to +140	o C

## Approvals

Declarations	
Standards Met	

## Similar Products

Stock No.	Brand	Product Name	Colour	Material