



MY4-GS 24VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

Specifications

Transparent case	✓
With mechanical indicator	✓
Mounting method	With plug-in socket
Usage	General purpose
Poles	4
Rated carry current	6 A
Coil voltage	24 V
Operation voltage	DC
Contact material	Ag
Contact description	4PDT
Terminal	Plug-in, Solder

Fits to



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

Downloads



Industrial Relays Brochure

EN PDF 1.46 MB



MY Miniature Power Relays Brochure

EN PDF 1.4 MB



MY-GS Datasheet

EN PDF 4.59 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 30 June, 2022. [Click here for terms of use.](#)