

3V, 5V & 8V SECTIONS

S=C PLUS LENGTH TOLERANCES

optibelt SK
V-BELTS, SINGLE



STANDARD V-BELTS
SK

SAMPLE PART # : 3V1060

STANDARD V-BELTS

3V SECTION : 3/8"W x 5/16"H

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
3V250	25	.10
3V265	26.5	.11
3V280	28	.11
3V300	30	.12
3V315	31.5	.13
3V335	33.5	.13
3V355	35.5	.14
3V375	37.5	.15

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
3V400	40	.16
3V425	42.5	.17
3V450	45	.18
3V475	47.5	.19
3V500	50	.20
3V530	53	.21
3V560	56	.22
3V600	60	.24

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
3V630	63	.25
3V670	67	.27
3V710	71	.28
3V750	75	.30
3V800	80	.32
3V830	83	.33
3V850	85	.34
3V900	90	.36

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
3V950	95	.38
3V1000	100	.40
3V1060	106	.42
3V1120	112	.45
3V1180	118	.47
3V1250	125	.50
3V1320	132	.53
3V1400	140	.56

SAMPLE PART # : 5V900

STANDARD V-BELTS

5V SECTION : 5/8"W x 17/32"H

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
5V500	50	.55
5V530	53	.58
5V560	56	.62
5V600	60	.66
5V630	63	.69
5V670	67	.74
5V710	71	.78
5V750	75	.83
5V800	80	.88

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
5V850	85	.94
5V900	90	.99
5V950	95	1.05
5V1000	100	1.10
5V1060	106	1.17
5V1080	108	1.19
5V1120	112	1.23
5V1180	118	1.30
5V1250	125	1.38

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
5V1320	132	1.45
5V1400	140	1.54
5V1500	150	1.65
5V1600	160	1.76
5V1700	170	1.87
5V1800	180	1.98
5V1900	190	2.09
5V2000	200	2.20
5V2120	212	2.33

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
5V2240	224	2.46
5V2360	236	2.60
5V2500	250	2.75
5V2650	265	2.92
5V2800	280	3.08
5V3000	300	3.30
5V3150	315	3.47
5V3350	335	3.85
5V3550	355	3.91

SAMPLE PART # : 8V2800

STANDARD V-BELTS

8V SECTION : 1"W x 7/8"H

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
8V1000	100	3.20
8V1060	106	3.39
8V1120	112	3.58
8V1180	118	3.78
8V1250	125	4.00
8V1320	132	4.22
8V1400	140	4.48
8V1500	150	4.80

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
8V1600	160	5.12
8V1700	170	5.44
8V1800	180	5.76
8V1900	190	6.08
8V2000	200	6.40
8V2120	212	6.78
8V2240	224	7.17
8V2360	236	7.55

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
8V2500	250	8.00
8V2650	265	8.48
8V2800	280	8.96
8V3000	300	9.60
8V3150	315	10.08
8V3350	335	10.72
8V3550	355	11.36
8V3750	375	12.00

PART NO.	OUTSIDE LENGTH (IN)	WEIGHT (LBS)
8V4000	400	12.80
8V4250	425	13.60
8V4500	450	14.40
8V5000	500	16.00
8V5600	560	17.92
8V6000	600	19.20

HAVE ANY QUESTIONS? CONTACT CUSTOMER SERVICE

800-292-6081 INFO@OPTIBELT-USA.COM

S=C Length Tolerances

Standard on all OPTIBELT single V-belts and Wedge belts 47" in length and above. S=C Plus V-belts are always superior to a matched-set regardless of the date manufactured. Not available on aramid cord, banded or cogged belts.

Custom Sizes & Ordering

Section / Max. Mfg Lengths / Min. qty.

- 3V / 157 in. / 40
- 5V / 475 in. / 25
- 8V / 708 in. / 14

Contact customer service for details.

Contact an OPTIBELT representative regarding additional sizes, stock availability and pricing.

All weights are estimated.

Additional sizes and stocking available.