




P.C.B. LAYOUT
(BOTTOM VIEW)



No.	Description	Material	Treat	數量
1	Housing	PBT		1
2	Base	PBT		1
3	GND Cont.	Copper	Nickel Ptd.	1
4	PIN EL	Brass	Tin Ptd.	1
5	PIN DL	Brass	Tin Ptd.	1
6	PIN CL	Brass	Tin Ptd.	1
7	PIN ER	Brass	Tin Ptd.	1
8	PIN DR	Brass	Tin Ptd.	1
9	PIN CR	Brass	Tin Ptd.	1
10	PIN A	Brass	Tin Ptd.	1
11	PIN B	Brass	Tin Ptd.	1

SPECIFICATION:
Insulation Resistance :
 100MΩ min. at 500V DC
Dielectric Strength :
 1,000V AC/1 minute
Contact Resistance :
 20mΩ Max.
Rating :
 2A 100V AC

品名: ITEM :	8P270 DIN SOCKET		 一般公差 .X +/-0.25 .XX +/-0.10	SHEET:  1 1	單位: unit:	mm	日期: date:	'07/01/23	繪圖: drwn by:	DanielShyr
	料號: PART NO.	491049			圖號: DRW NO.		比例: scale:	3:2	版本: version:	V. 1.0