

## FEATURES

- Mini foot Switch made in ABS V0 plastic material
- Black cover and black base
- Free movement of the lever
- Very sturdy and reliable also in harsh environment

## RS PRO mini foot switch, black plastic cover, free movement of the lever, snap action contacts, Gland Ø6 inlet

RS Stock No.: 2380554



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Foot Switches

### Product Description

Mini Foot switch used to command machineries and equipment in industrial environment. Suited for applications that requires sturdy and reliable products.

### General Specifications

Casing Material	ABS V0
Class II - Double insulation	Gland Ø6
Operating head	Plastic lever
Microswitch	1NO+1NC changeover
Connecting Terminals	Screws with washere M3x0.5 (+, -) Philips head
Connecting Cables Dimensions [mm <sup>2</sup> ]	0,34 ... 1,5

### Mechanical Specifications

Operating Temperatures [°C]	-25 / +70
Stock Temperatures [°C]	-30 / +80
Mechanical durability (Millions of operations)	1
Electrical durability (Millions of operations)	0.1
Max. switching frequency [Cicli/h]	3600

### Electrical Specifications

Protection against electrical shocks	Class II - Double insulation
Rated Insulating Voltage $U_i$ [V]	250
Pollution Degree	3
Contact rating secondo UL508	Class II device
Rated impulsive voltage [kV]	1
Conventional thermal current in air free $I_{th}$ ( $\theta$ min 40 ° C) [A] ( $\theta$ )	15
Short circuit protection (EU min 500Vac - fuses type gG (g)) [A]	10
Rated Operational Current $I_e$ - AC-15 (50-60 Hz) [Vac - A]	256V - 3A
Rated Operational Current DC-13 [Vdc - A]	236V – 0.06A
Resistance Between Contacts [mΩ]	30

**Protection Category**

IP Degree of Protection	40
-------------------------	----

**Additional Information**

EAN	8000126233360
Custom Tariff Number	85371098

**Approvals**

Declarations	CE – UKCA
Standards Met	IEC 1058-1 and IEC 61058-7