



EB-Certalume for PLT/C lamps

EB-C 113 PL-T/C 220-240V 50/60Hz

Affordable, reliable, high frequency electronic ballast for 4-pin PL-T and PL-C fluorescent lamps, ideal alternative for electromagnetic (EM) ballasts

Product data

Operating and Electrical				
Input Voltage	220 to 240 V			
Line Frequency	50 to 60 Hz			
Input Frequency	50 to 60 Hz			
Number of Products on MCB (16A Type	20			
B) (Nom)				
Wiring				
Connector Type Input Terminals	250 manual connector [Suitable for manual			
	wiring and easy release button]			
Color Input Terminals	Orange			
Color Output Terminals	Grey			
Connector Type Output Terminals	250 manual connector [Suitable for manual			
	wiring and easy release button]			
Temperature				
T-Case Lifetime (Nom)	65 °C			


65 °C

Approval and Application					
Ingress protection code	IP20 [Finger-protected]				
Energy Efficiency Index	A2				
Approval Marks	CCC certificate CB Certificate				
Product Data					
Full product code	872790083286000				
Order product name	EB-C 113 PL-T/C 220-240V 50/60Hz				
Order code	913713198414				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	24				
Material number (12NC)	913713198414				
Full product name	EB-C 113 PL-T/C 220-240V 50/60Hz				
EAN/UPC - Case	8727900832860				

T-Case Maximum (Max)

EB-Certalume for PLT/C lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
EB-C 113 PL-T/C 220-240V 50/60Hz	4.2 mm	31.0 mm	94.0 mm	86.0 mm	72.0 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 17 - data subject to change