



SMT-2212



Key Features

- 22" FHD Monitor, support up to 1920*1080 60Hz (FHD)
- Brightness 250 cd/m² (Typ) . Contrast 2000:1(Min), 3000:1(Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 6.5ms(Typical)
- Video Input : HDMI(1), VGA(1)
- Frameless design with monitor stand
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation



SMT-2212

Specifications

Display

Type	LED Monitor
Screen Size	22inch
Max. Resolution	1920x1080
Brightness	250 cd/m ²
Contrast Ratio	3000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	6.5ms
Panel Life	30,000 hours

Interface

Video	Connectors	VGA(1), HDMI(1)
VGA	Connector	VGA
	Available Format	1920x1080@60Hz
HDMI	Connector	HDMI
	Available Format	1920x1080@60Hz

On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

General

Electrical	Input Voltage	DC 12V 5A, Adapter included
	Power Consumption	30W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)

General

Mechanical	Dimensions with Stand (WxHxD)	491.9x186.7x371.4mm(19.4x7.4x14.6")
	Dimensions without Stand (WxHxD)	491.9x36.1x289.4mm(19.4x1.4x11.4")
	Weight	2.59Kg(5.7lb)
	Packing Dimension (WxHxD)	542*106*352mm(21.3x4.2x13.9")
	Packing Weight	3.13Kg(6.9lb)
	Cabinet Color	Black
	VESA Mounts Interface	100x100mm

SMT-2212



CAD

Unit: mm [inch]

SMT-2212

