



### Main

Product or component type	Connection unit
Load type	Inductive Resistive
Cover frame colour tint	White

### Complementary

Width	87 mm
Height	87 mm
Depth	30 mm
Wiring device mounting	Flush Surface
Rated current	25 A at 250 V AC 50 Hz
Material	Polycarbonate + 20 % FG: grid plate Polycarbonate: base Polycarbonate: surround
Contacts material	Contact: brass and phosphor bronze
Connections - terminals	Pillar terminals
Number of cables	1 cable(s) 16 mm <sup>2</sup>

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	BS 5733

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	181.56 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.289 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	60

Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	13393.6 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------