


Instrumentation Grade SMD Reed Relay

RoHS
Compliant



Schematic View



Features

- High reliability instrumentation grade reed switch with sputtered Ruthenium contacts for stable contact resistance and long life
- 10W 1 Form A available in Gull Wing lead configuration
- Standard coaxial shield for RF applications up to 6GHz
- External magnetic shield
- High insulation resistance

Contact Form: 1 Form A

Coil Data

Nominal Coil Voltage (V DC)	Nominal Coil Resistance $\pm 10\% \Omega$	Max. Operating Voltage (V DC)	Min. Release Voltage (V DC)	Max. Coil Voltage (V DC)
5	150	3.8	0.4	6

Contact Rating

Switching Power (Max.)	: 10W
Switching Voltage (Max.)	: 170V DC / 120V AC RMS
Switching Current (Max.)	: 0.5A
Carrying Current (Max.)	: 1A


Specifications

Contact Resistance (Initial) (Max.)	: 150m Ω
Operate Time-Including Bounce Time (Typ.)	: 0.25ms (@ Nominal Voltage)
Release Time (Typ.)	: 0.05ms
Insulation Resistance @ 100V DC (Min.)	: 10 ¹² Ω (Min.)
Dielectric Strength (Min.)	: Between Open Contacts 210V DC/peak AC All Other Points 1500V DC/peak AC
Capacitance (Typ.)	: 0.2pF
Vibration	: 20G (10 ~ 2kHz, 1.5mm)
Shock	: 50G
Operating Temperature	: -40°C to +85°C
Storage Temperature	: -35°C to +100°C
Life Expectancy @ Specified Load	: 100 × 10 ⁶ ops (1V DC, 10mA)

www.element14.com
www.farnell.com
www.newark.com

Instrumentation Grade SMD Reed Relay

Dimensions



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
Reed Relay, SPST-NO, 5V DC, 150Ω, 170V DC/120V AC, 0.5A, SMD	MCCGSM-051A-G

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com
www.farnell.com
www.newark.com

