



### Main

Range of product	Altivar
Product or component type	Communication module

### Complementary

Range compatibility	Altivar&nbsp;Process ATV600 Altivar Machine ATV340 except Sercos drives Altivar Machine ATV320 Altivar 32 Altivar Process Modular Altivar&nbsp;Process ATV900
Communication port protocol	Link Layer Discovery Protocol PROFINET
Electrical connection	2 connectors RJ45, Ethernet
Transmission rate	100 Mbps
Display type	1 LED for MS (Module Status) 1 LED for NS (Network Status) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for TX/RX (Transmit/Receive port 2)
Bus profile	PROFIdrive
Net weight	0.3 kg

### Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 cm
Package 1 Width	6.500 cm
Package 1 Length	8.900 cm
Package 1 Weight	63.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.700 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes