



Main

Range	TeSys
Product name	TeSys Mini-VARIO
Device short name	VCCDN
Product or component type	Emergency stop switch disconnecter
Performance level	Standard
Poles description	3P
Contacts type and composition	3 NO
Network type	DC AC
Control type	Rotary handle
Rotary handle mounting style	Extended
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 4...8 mm

Complementary

Marking	0 - 1
Mounting support	Handle: door Switch: symmetrical rail
Fixing mode	Hole with 22.5 mm for handle By clips for switch
[Ith] conventional free air thermal current	20 A
[Ithe] conventional enclosed thermal current	16 A
[Ie] rated operational current	11 A (AC-23) at 400 V
Rated operational power in W	4 KW at 230...240 V (AC-23A) 5.5 KW at 400...415 V (AC-23A) 7.5 KW at 500 V (AC-23A) 11 KW at 690 V (AC-23A) 3 KW at 230...240 V (AC-3) 4 KW at 400...415 V (AC-3) 5.5 KW at 500 V (AC-3) 5.5 kW at 690 V (AC-3)
Intermittent duty class	30
Making capacity (I Rms)	200 A at 400 V AC-21A 200 A at 400 V AC-22A 200 A at 400 V AC-23A
[Icm] rated short-circuit making capacity	0.5 kA at 400 V at Ipeak
[Icw] rated short-time withstand Rms current	140 A at 400 V duration: 1 s
Rated conditional short-circuit current	6 KA at 400 V - associated fuse 20 A aM 6 kA at 400 V - associated fuse 20 A gG
Breaking capacity	200 KA at 400 V (AC-21A) 200 KA at 400 V (AC-22A) 200 kA at 400 V (AC-23A)
Device composition	Shaft extension Handle Switch
Mechanical durability	50000 cycles

Electrical durability	30000 Cycles DC-1...5 50000 cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit: screw clamp terminals 4 mm ² - flexible - with cable end Power circuit: screw clamp terminals 4 mm ² - solid
Tightening torque	Power circuit: 0.7 N.m - on screw clamp terminals
Handle front plate dimension	60 x 60 mm
Height	60 mm
Width	60 mm
Net weight	0.334 kg

Environment

Standards	IEC 60947-3
Product certifications	GL CSA CCC UL
Protective treatment	TC
IP degree of protection	IP65
Mechanical robustness	Shocks 11 ms (15 gn) conforming to IEC 60068-2-27 Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------