HU361AWK

Safety switch, heavy duty, non fusible, 30A, 3 wire, 3 pole, 30hp, 600VAC/DC, NEMA 12





Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Network number of phases	3 phases
Number of Poles	3
Current Rating	30 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R/12 galvannealed steel
Motor power hp	5 Hp at 240 V AC 5060 Hz for 1 phase motors 10 Hp at 240 V AC 5060 Hz for 3 phases motors 7.5 Hp at 480 V AC 5060 Hz for 1 phase motors 20 Hp at 480 V AC 5060 Hz for 3 phases motors 10 Hp at 600 V AC 5060 Hz for 1 phase motors 30 Hp at 600 V AC 5060 Hz for 3 phases motors 5 Hp at 250 V DC 15 hp at 600 V DC

Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper	
Tightening torque	5.08 N.M for 13.3 mm² (AWG 6) 4.52 N.M for 8.367 mm² (AWG 8) 3.95 N.m for 2.065.261 mm² (AWG 14AWG 10)	
Depth	125.98 mm	
Width	191.77 mm	
Height	370.84 mm	
Product weight	5 kg	

Environment

Certifications	UL listed file E2875

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	13.97 cm	
Package 1 Width	19.558 cm	
Package 1 Length	44.45 cm	
Package 1 Weight	4.513 kg	
Unit Type of Package 2	PAL	
Number of Units in Package 2	96	
Package 2 Height	116.84 cm	
Package 2 Width	101.6 cm	

Package 2 Length	121.92 cm
Package 2 Weight	444.52 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------