



Datasheet

RS PRO Fully-Coated Ladder Single-Lock Stainless Steel Cable Ties

EN

STOCK NO: 1834173, 1834174



Technical Information:

Material: Stainless Steel Grade 316

316 grade stainless steel, for extra corrosive environments

Coating: Polyester

Working Temp.: -80° C to $+150^{\circ}$ C

Description: Entirely Black **Flammability:** Fireproof

Other Properties: UV-resistant, Halogen free, non toxic

Product Feature: Strong self-locking mechanism(Pawl and ratchet) saves time on installation;

Flat and low profile head(no sharp edge), for easy installation;

Larger slot at the end, allows the use of a hook-type tool.

Fully coated version provide additional edge protection;

Applications: Ideal for petrochemical, industries, power stations, mining, ship-building, offshore, and other aggressive environments.

Specification

Specification.											
RS CODE	EASE CODE	LENGTH		WIDTH		TICKNESS		MAX. BUNDLE DIAMETER		MIN. TENSILE STRENGTH	
		mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
1834172	CT-SS-LS- 225/7FC	225	8.9	7.0	0.28	0.4	0.016	62	2.44	350	78
1834173	CT-SS-LS- 300/7FC	300	11.8					81	3.19		
1834174	CT-SS-LS- 610/7FC	610	24.0					176	6.93		



