

# Power Inlet with Fuse Holder



**RoHS  
Compliant**

## Specifications

### Material:

Moulding	: Nylon, Flammability Rating UL 94 V-0
Contacts	: Brass, Pins Nickel Plated, Tags Tin Plated
Rating	: 10A, 250V AC
Contact Resistance	: <10mΩ
Insulation Resistance	: >100MΩ 500V DC Min.
Dielectrics Strength	: 2000V AC/1mA 1Min.


### A.C. Breakdown:

Pole-Pole	: 5kV
Poles-Panel	: 4kV
Operating Temperature	: -10°C to +60°C
Fuses Size	: 5mm × 20mm (Not Included)
Screw Size	: M3

Dual Fuse Holder, One Active, One Spare



## Diagram



## Part Number Table

Description	Part Number
Power Inlet with Fuse Holder, 10A, 250V AC, 1-Pole Fuse Holder	2147

Dimensions : Millimetres

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands  
Farnell.com/exclusive-brands  
Element14.com/exclusive-brands

