

Kanazawa Hand Chain Hoist – Model KSB Series



- Meets or exceeds all industrial standards including EN13157:2003 and ASME/ANSI B30.21 requirements.
- Conforms to Machinery Directive 98/37/EC.
- Two ratchet pawls for extra safety.
- Both hooks are hot forged, heat treated swivel, and equipped with safe latch.
- Leaf chain container available to special order.

Stock Code		AQ01057	AQ01059	AQ01061	AQ01063	AQ01065	AQ01067	AQ01068	AQ01069	AQ01070	AQ01071
Capacity	Ton	0.5	1.0	1.5	2.0	3.0	5.0	7.5	10.0	15.0	20.0
Standard Lift	m	2.5	2.5	2.5	3	3	3	5	5	5	5
Proof test load	KN	7.3	14.7	29.4	29.4	44	73.5	117.6	147	220.5	294
Effort required to lift rated load	kg	16	32	33	32	34	42	42	45	47	45
No. of columns of load chain		1	1	1	1	2	2	4	4	8	8
Load Chain	mm	6 x 18	6 x 18	8 x 24	6 x 18	10 x 30	10 x 30	10 x 30	10 x 30	10 x 30	10 x 30
Dimensions (mm)	Amin	295	345	450	440	530	620	735	735	1000	1000
	B	16	21	37	27	46	45	60	60	85	85
	C	22	27	37	30	46	46	52	52	74	74
	D	11	15	25	20	29	30	40	40	56	56
	F	125	147	183	147	215	215	360	360	590	590
	Fl	213	232	314	232	333	333	-	-	-	-
	G	-	-	-	-	-	-	252	252	-	-
	H	-	-	-	-	-	-	108	108	108	108
	J	111	125	142	125	163	163	163	163	198	198
	J1	146	153	174	153	179	179	-	-	-	-
	K	52	57	68	57	79	79	79	79	-	-
	L	59	68	74	68	84	84	84	84	99	99
	M	195	224	266	231	316	334	-	-	-	-
N	260	260	310	260	310	310	-	-	-	-	
O	140	140	200	140	200	200	-	-	-	-	
P	110	110	130	110	130	130	-	-	-	-	
Net weight		9	11	18	15	28	39	70	74	85	105