

Product may differ from Image

## HWWI 3500/25 Inox (600970000) Domestic waterworks (220-240 V / 50 Hz); Cardboard box

Order no. 600970000 EAN 4007430239525



- Complete system in compact design with integrated filter and check valve integrated as standard for easy installation
  For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Pressure vessel for energy-saving and low-noise provision of water
- Electronic pressure switch at the boiler for automatic activation in case of increased water demand
- Metabo pump protection: automatic dry-run protection with LED display to protect the pump and high user safety
- Integrated, washable filter protects the pump from contamination
- Integrated check valve prevents dry running of the pump when it is switched off, enabling a short restart process
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Durable stainless steel pump housing
- Separate water filling opening for simple operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- For garden irrigation with 1 or 2 sprinklers
- For single phase alternating current

## Technical data

## Characteristics

Rated input power	1100 W
Maximum delivery rate	3500 l/h / 925 gal/h
Maximum delivery height	45 m / 148 ft
Maximum pressure	4.5 bar / 65.3 psi
Maximum suction height	8 m / 26 ft
Switch-on pressure approx.	1.6 bar / 23.2 psi
Switch-off pressure approx.	4.5 bar / 65.3 psi
Suction port	1" female thread
Discharge port	1" female thread
Tank capacity, approximately	24 l / 6.3 gal
Pump housing	Stainless steel
Protection type IP	IP X4
Drive shaft	Stainless steel
Tank	Steel
Number of impellers	1
Dimensions	520 x 307 x 600 mm // 20 15/32 x 12 3/32 x 23 5/8 "
Weight	17.5 kg / 38.6 lbs
Cable length	1.5 m / 5 ft
Noise emission	
Sound pressure level	65 dB(A)
Sound power level (LwA)	77.8 dB(A)
Uncertainty of measurement K	2.5 dB(A)

## Scope of delivery

Fabric Sealing Tape Filter Key