



Main

| | |
|-------------------------------------|---|
| Range | Acti9 |
| Product name | Acti9 iID |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | iID |
| Poles description | 4P |
| Neutral position | Left |
| [In] rated current | 40 A |
| Network type | AC |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC |

Complementary

| | |
|---|---|
| Device location in system | Outgoer |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 380...415 V AC 50/60 Hz |
| Residual current tripping technology | Voltage independent |
| Rated breaking and making capacity | I _{dm} 1500 A I _m 1500 A |
| Rated conditional short-circuit current | 10 kA |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Contact position indicator | Yes |
| Control type | Toggle |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 8 |
| Height | 91 mm |
| Width | 72 mm |
| Depth | 73.5 mm |
| Net weight | 0.37 kg |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | AC-1: 15000 cycles |
| Locking options description | Padlocking device |
| Connections - terminals | Single terminal top or bottom 1...35 mm ² rigid Single terminal top or bottom 1...25 mm ² flexible Single terminal top or bottom 1...25 mm ² flexible with ferrule |
| Wire stripping length | 14 mm for top or bottom connection |
| Tightening torque | 3.5 N.m top or bottom |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 61008-1 |
| Product certifications | SNI |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 3 |
| Electromagnetic compatibility | 8/20 μ s impulse withstand, 250 A conforming to EN/IEC 61008-1 |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.3 cm |
| Package 1 Width | 9.9 cm |
| Package 1 Length | 7.6 cm |
| Package 1 Weight | 359 g |

Offer Sustainability

| | |
|-------------------|--|
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
|-------------------|--|