

## Datasheet

# RS Pro Non-Fused Terminal Block, 3 Way/Pole, Screw Terminals, 2.5 mm<sup>2</sup> Panel Mount, PA, 400 V

RS Stock No: **868-0777**



## Product Details

RS Pro non-fused terminal block in white colour, comes with an earth connection, which is made via an M4 x 10 hole within a centrally mounted block. This 3-way terminal block made of polyamide material, features screw termination. This terminal block with 2.5-mm<sup>2</sup> wire, features nickel plated brass contact. The panel mount block has a voltage rating of 400 V.

## Features and Benefits

- Self-extinguishing of UL 94 V-2, IEC 695-2-1 to 850°C, IEC 695-2-2
- Maximum operating temperature of 100°C
- Short-time temperature of 160°C
- Test voltage of 2500 V
- Test current of 24 A
- galvanised steel M 3 x 6 screws



ENGLISH

### Specifications:

Contact Material	Brass
Contact Plating	Nickel
Enclosed	No
Material	Polyamide Housing
Maximum Operating Temperature	+100°C
Mounting Type	Panel Mount
Number of Ways	3
Termination Method	Screw
Voltage Rating	400 V
Wire Size	2.5 mm <sup>2</sup>
Colour	White
Screw Size	M3 x 6
Standards Met	RoHS, UL 94V-2, IEC 695-2-1, IEC 695-2-2, EN 60998-1, EN 60998-2-1