Product data sheet Characteristics

A9MEM2100

modular single phase power meter iEM2100 - 230V - 63A



Main	
Range	Acti9
Family	Acti9 iEM2100
Device short name	iEM2100
Product or component type	Energy meter

Complementary

Poles description	1P + N
Type of measurement	Active energy
Device application	Sub billing
Accuracy class	Class 1 active energy conforming to IEC 62053-21
Input type	Direct input
Maximum current [Imax]	63 A
[lb] basic current	10 A
Rated current	63 A
Rated voltage	230 V +/- 20 %
Network frequency	60 Hz 50 Hz
Frequency measurement range	4565 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	0.563 A
Display digits	5
Maximum value measured	999.99 MWh
Tariff counter	Tariff (1)
Communication port protocol	-
Communication port support	-
Local signalling	Green indicator light: power ON Yellow indicator light: metering and activity 1000 p/kWh
Digital inputs	0
Maximum power consumption in VA	2.5 VA at 240 V AC
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Power circuit: tunnel type terminals (bottom) 1 16 mm² cable(s)
Tightening torque	Power circuit: 1.5 N.m
Standards	IEC 61557-12 IEC 62053-21
Product certifications	CE

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 casing:	
IK degree of protection	IK05	
Ambient air temperature for operation	-2555 °C -2055 °C	
Ambient air temperature for storage	-2570 °C	
Operating altitude	< 3000 m	
Relative humidity	095 % at 55 °C	
Colour	White	
9 mm pitches	4	
Width	36 mm	
Height	81 mm	
Depth	65 mm	
Net weight	0.135 kg	

Packing Units

· doming or mo	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.8 cm
Package 1 Width	9.5 cm
Package 1 Length	4.5 cm
Package 1 Weight	172 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	11.399 kg
Unit Type of Package 3	P06
Number of Units in Package 3	480
Package 3 Height	105 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	82.6 kg

Offer Sustainability

EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes