

Eaton FWP-1A14F

Catalog Number: FWP-1A14F

Eaton Bussmann series FWP high speed fuse, 700V (UL), 1A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-1A14F
	UPC
	051712795098
EAN	Product Length/Depth
5027590500272	51 mm
Product Height	Product Width
15 mm	15 mm
Product Weight	Warranty
20.6 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

Product specifications

Interrupt rating

200 kAIC

Release characteristic

Other

Amperage Rating

1 A

Frequency rating - max

62 Hz

Fuse type

FWP-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Fuse size

14 x 51 mm

Voltage rating

700 V

Fuse indicator

Non Indicating

Construction size

14 mm x 51 mm

Clearing (I2T)

0.41

Color

White

Connection

Ferrule end x ferrule end

Material

Ceramic

Utilization category

aR (accompanied semiconductor protection)

Watt losses

5.7 W

Type

High speed fuse

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720025 FWP

Fuse shape

Cylindrical

Breaking capacity

200 kA

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

0.04

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)