



## PRO-FIT reducing bush PVC-U metric

### Model:

- Outlet: A and B = Solvent cemented spigot in combination with reducing socket metric

d	d1	d3	PN	d2	Part No.	SP	weight	z	z1	z2	L
(mm)	(mm)	(mm)	(bar)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)
10	14	12	16	8	<b>721 910 903</b>	10	0.003	15	15	3	27
12	16	12	16	8	<b>721 910 905</b>	10	0.004	18	18	6	30
12	16	16	16	10	<b>721 910 906</b>	10	0.004	18	18	6	30
16	20	16	16	10	<b>721 910 908</b>	10	0.003	21	19	7	33
16	20	16	16	12	<b>721 910 909</b>	10	0.004	21	19	7	33
20	25	16	16	12	<b>721 910 910</b>	10	0.008	25	21	9	37
20	25	20	16	16	<b>721 910 911</b>	10	0.008	25	23	9	39
25	32	16	16	12	<b>721 910 912</b>	10	0.014	30	23	11	42
25	32	20	16	16	<b>721 910 913</b>	10	0.015	30	26	12	44
25	32	25	16	20	<b>721 910 914</b>	10	0.017	30	27	11	46
32	40	20	16	16	<b>721 910 915</b>	10	0.025	36	28	14	50
32	40	25	16	20	<b>721 910 916</b>	10	0.026	36	30	14	52
32	40	32	16	25	<b>721 910 917</b>	10	0.031	36	33	14	55
40	50	25	16	20	<b>721 910 918</b>	10	0.045	44	34	18	60
40	50	32	16	25	<b>721 910 919</b>	10	0.052	44	37	18	63
40	50	40	16	32	<b>721 910 920</b>	10	0.058	44	40	18	66
50	63	32	16	25	<b>721 910 921</b>	5	0.092	54	42	23	73
50	63	40	16	32	<b>721 910 922</b>	5	0.098	54	45	23	76
50	63	50	16	40	<b>721 910 923</b>	5	0.111	54	49	23	80
63	75	40	16	32	<b>721 910 924</b>	5	0.127	62	46	24	84
63	75	50	16	40	<b>721 910 925</b>	5	0.139	62	50	24	88
63	75	63	16	50	<b>721 910 926</b>	1	0.167	62	55	24	93
75	90	50	16	40	<b>721 910 927</b>	10	0.224	74	56	30	100
75	90	63	16	50	<b>721 910 928</b>	10	0.253	74	61	30	105
75	90	75	16	63	<b>721 910 929</b>	10	0.265	74	68	30	112

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>