
Laminated Solenoid

multicomp PRO

RoHS Compliant



Specifications


Temperature Range Relative Humidity Rated Voltage Sphere of Application

:	-20°C to +60°C
:	20% to 85%
:	220V AC (50/60Hz)
:	Intermittent

Electrical Specifications

Current	: 2.58A (ref)
Resistance	: 85Ω±10% @ 20°C
Insulation Resistance	: 200MΩ Min, 500V AC
Insulation Level	: Class F (155°C)
Potence	: 220V AC, when the stroke is 15mm, the power is 1.7K
High Voltage	: 1800V AC
Life	: More than 100,000 times under normal use

Diagram



Part Number Table

Description	Part Number
Laminated Solenoid, 220V AC, 2.58A, 1.7N	MP001151

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

5,6

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

