

Main

Range	ZENcelo
Product or component type	Data socket
Device application	Communication
Colour tint	White

Complementary

Rated current	1.5 A
Communication network category	Data: 6e
Insulation resistance	>= 200 MOhm
Contact resistance	1 µOhm
Number of gangs	1 gang
Minimum return loss	23 dB
AWG gauge	AWG 26...AWG 22 (4 twisted pair cables)
Contacts material	Housing: PC Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate: plastic part
Device mounting	Flush Surface
Width	87 mm
Height	87 mm
Depth	36 mm

Environment

Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	1...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	91.36 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm

Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	930.88 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	9808.8 g