

# SYNTEX 500

## Fire Hose - White Type 1















### Construction

- 100% High tenacity polyester yarn, circular-woven (reinforcement)
- Circular woven twill weave, warp threads multiple twisted
- High quality, very light synthetic rubber on the basis of EPDM

MADE IN GERMANY

### Features

- Absolute tough, durable & very abrasion resistant
- Seawater resistant, weather resistant
- Aging and ozone resistant
- Temperature range -40 °C up to +100 °C
- Minimum friction loss because of very smooth inner lining
- Light and flexible
- Suitable for sea water, hot water and many chemicals


| DIAMETER     | WORKING PRESSURE | BURSTING PRESSURE | WEIGHT | APPROVALS   | PART NO      |
|--------------|------------------|-------------------|--------|---|--------------|
| 38MM / 1.5"  | 16BAR            | 60BAR             | 210G   | GL    | HO-T1-SSO-15 |
| 45MM / 1.75" | 16BAR            | 60BAR             | 240G   | GL    | HO-T1-SSO-17 |
| 52MM / 2.0"  | 16BAR            | 60BAR             | 290G   | GL    | HO-T1-SSO-20 |
| 65MM / 2.5"  | 16BAR            | 60BAR             | 365G   | GL   | HO-T1-SSO-25 |
| 70MM / 2.75" | 16BAR            | 60BAR             | 395G   | GL   | HO-T1-SSO-27 |
| 75MM / 3.0"  | 16BAR            | 60BAR             | 475G   | GL   | HO-T1-SSO-30 |



Germanischer  
Lloyd



DIN 14540: 2007



Wheelmark

Due to constant improvements, product dimensions may differ slightly.



**FIRE ARMOUR**

14 Fan Yoong Rd, Singapore 629791 T 62666788 F 62663788  
Email: firearmour@firearmour.com.sg