Cable Assembly U.FL - SMA, IP67, 300mm



RoHS Compliant




Specifications:

Electrical Performance

Impedance : 50Ω

Frequency Range : DC to 3 GHz Max. Working Voltage : 60V rms Min. Dielectric Withstanding Voltage : 200V rms Min. Insulation Resistance : $500M\Omega$ Cable Length : 300mm External Diameter : 1.37mm Cable Colour : Black

Diagram



Dimensions : Millimetres

Item	Description	
1	SMA B/H Jack Crimp Type for \phi1.37mm Cable (Nut × 1, Washer × 1)	
2	Heat Shrink Tube F32 \(\phi 2.5mm L = 10mm \) Colour: Black	
3	φ1.37mm Cable Tin Plated Colour : Black	
4	U.FL-LP-088 Shell for φ1.37mm Cable	
5	U.FL-LP-088 Terminal for φ1.37mm Cable	

Part Number Table

Description	Part Number
Cable, U.FL - SMA, IP67, Length 300mm	R-132G7210300CA

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Page <1>

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

