

FEATURES

- WATERTIGHT
- INDESTRUCTIBLE
- FOR PROFESSIONAL USE
- PROTECTIVE
- MILITARY GRADE
- WITH PRE-CUBED FOAM
- STACKABLE

RS PRO Flight Cases & Equipment Cases

RS Stock No.: 2537423, 2537424, 2537426, 2537427, 2537428, 2537429, 2537430, 2537431, 2537432, 2537433, 2537434, 2537435, 2537436, 2537437, 2537438, 2537439



Airtight containers, resistant to chemicals, moisture and dust. Resistant to the most extreme temperatures (-33 ° C / + 90 ° C).

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

WATERPROOF CASE IN COPOLYMER POLYPROPYLENE

Indestructible cases recommended for professional use.

REMOVABLE LID WITH SAFETY LOCK

To remove the cover, simply tilt it at 70 ° after releasing the screws on the hinges rear

REINFORCED HINGES WITH ANTI CORROSION METAL PIN

STURDY CLOSURES

SEALING O-RING AND MANUAL PRESSURE RELEASE VALVE

ID REMOVABLE PLATE

ANTI TILT SUPPORTS (in some models)

WITH PRECUBED FOAM INSIDE


SELF OILING FREE RUNNING WHEELS

EASY TO OPEN RELEASE TELESCOPIC HANDLE

TWO MAN LIFT SIDE HANDLES

General Specifications

METRIC MM-KG-C°



INTERNAL DIMENSIONS

L LENGTH	765 mm
W WIDTH	485 mm
D DEPTH	305 mm
LID	60 mm
BASE	245 mm


EXTERNAL DIMENSIONS

L LENGTH	860 mm
W WIDTH	560 mm
D DEPTH	355 mm

OTHER DATA

WEIGHT EMPTY	13.56 Kg
WEIGHT WITH FOAM	16.39 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	113.10 lt
BUOYANCY	81.80 Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS

L LENGTH	30 1/8 in
W WIDTH	19 1/8 in
D DEPTH	12 in
LID	2 3/8 in
BASE	9 5/8 in

EXTERNAL DIMENSIONS

L LENGTH	33 7/8 in
W WIDTH	22 1/16 in
D DEPTH	14 in

OTHER DATA

WEIGHT EMPTY	29.89 lbs
WEIGHT WITH FOAM	36.13 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	29.85 gal
BUOYANCY	180.33 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194