



HPI-T High Wattage

HPI-T 1000W/543 E40 1SL/4

Quartz metal halide lamps with clear outer bulb

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury lamps
- For use with control gear designed for high-pressure mercury lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information			
Cap-Base	E40 [E40]		
Operating Position	P [Parallel or Horizontal(HOR)]		
Life to 50% Failures (Nom)	12,000 hour(s)		
Light Technical			
Color Code	543 [CCT of 4300K]		
Color Designation	Cool White (CW)		
Chromaticity Coordinate X (Nom)	370		
Chromaticity Coordinate Y (Nom)	380		
Correlated Color Temperature (Nom)	4300 K		
Luminous Efficacy (rated) (Nom)	83 lm/W		

Color rendering index (CRI)	57
Arc Length O (Nom)	80 mm
Operating and Electrical	
Power Consumption	990 W
Voltage (Nom)	130 V
Voltage (Nom)	130 V
Controls and Dimming	
Dimmable	No
Voltage (Nom) Voltage (Nom) Controls and Dimming	130 V 130 V


Datasheet, 2023, April 16 data subject to change

HPI-T High Wattage

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T65 [T 65mm]
Approval and Application	
Mercury (Hg) Content (Nom)	86 mg
Energy Consumption kWh/1000 h	1089 kWh
Product Data	
Order product name	HPI-T 1000W/543 E40 1SL/4


Full product name	HPI-T 1000W/543 E40 1SL/4
Full product code	871150018373645
Order code	928482600096
Material Nr. (12NC)	928482600096
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500183736
Numerator - Packs per outer box	4
EAN/UPC - Case	8711500183743

Dimensional drawing



Product	D (max)	0	L	C (max)
HPI-T 1000W/543 E40 1SL/4	66 mm	80 mm	240 mm	382 mm


Photometric data




Spectral Power Distribution Colour - HPI-T 1000W/543 E40 1SL/4

HPI-T High Wattage

Lifetime





Life Expectancy Diagram - HPI-T 1000W/543 E40 1SL/4

Lumen Maintenance Diagram - HPI-T 1000W/543 E40 1SL/4

