



### Main

Range of product	Acti 9 Librio Prodis Clario
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
[In] rated current	3 A: 380...415 V AC - 50/60 Hz 6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC
9 mm pitches	1

### Complementary

Range compatibility	Acti 9 DPN Vigi Acti 9 iDPN Vigi Acti 9 C60H-DC Acti 9 C60PV-DC Acti 9 C40 Acti 9 ID C40 Acti 9 C120 Acti 9 DT40 Acti 9 DT60 Acti 9 IDc Acti 9 C120NA-DC Acti 9 iDPN Acti 9 ITG40 Acti 9 SW60-DC Acti 9 C60NA-DC Acti 9 C40 Vigi Acti 9 DT40 Vigi
Mounting mode	Fixed
Mounting support	DIN rail

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	85.3 mm
Width	9 mm
Depth	73.5 mm
Net weight	30 g
Colour	White
Connections - terminals	Clamp terminal (bottom) 2 cable(s) 1.5 mm <sup>2</sup> - flexible Clamp terminal (bottom) 1 cable(s) 0.5...2.5 mm <sup>2</sup> - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

## Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASTA LCIE KEMA ASEFA
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	38 g
Package 1 Height	2 cm
Package 1 width	8 cm
Package 1 Length	9.4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	514 g
Package 2 Height	8.7 cm
Package 2 width	10 cm
Package 2 Length	26.5 cm
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	5.13 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---