Eaton LPJ-30SPI

LOW-PEAK

Catalog Number: LPJ-30SPI

Eaton Bussmann series LPJ fuse, 30 A, Dual, Class J, With indicator, Ferrule end x ferrule end, Time delay|Current-limiting, 10 sec at 500%, 300 kAIC at 600 V|100 kAIC Vdc, Standard

General specifications



Catalog Number

Eaton Bussmann series LPJ fuse

LPJ-30SPI

UPC

EAN

051712626354

5027590245340

Product Length/Depth

Product Height

0.81 in

2.25 in

Product Width

Product Weight

0.81 in

0.18 lb

Warranty

Compliances
CE Marked

Not Applicable

RoHS Compliant



Electrical rating

Amperage Rating

30 A

Interrupt rating

100 kAIC Vdc

300 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Fuse type

Time delay

Current-limiting

Number of elements

Dual

Packaging type

Standard

General information

Class

Class J

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

With Indicator

Special features

Non-indicating, High in-rush current motor protection

Resources

Catalogs

LPJ-30SPI~LOW PEAK CLASS J T/D

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - LPJ-30SPI

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia