



# Datasheet Ankernut

ENGLISH



## Features

The Ankernut is a synthetic rubber sleeve with a flange head and a brass threaded insert at the opposite end. They are mainly used in hollow base materials where the anchor can expand in the cavity. It is possible to use longer Ankernuts in solid material but a minimum embedment of 40mm is required.

## Typical Applications

Suspended services from hollow concrete planks, pipes, fan coils, cable tray and ventilation ductwork. Brackets and services from hollow block walls or perforated brick walls, also attachments to metal box section, metal angle and steel sheet.

## RANGE DATA

RANGE DATA							
Part Number	THREAD DIAM	HOLE DIAM	WALL THICK.	OVERALL LENGTH	FLANGE THICK.	FLANGE DIAM	TIGHT. TORQUE
	mm	mm	mm	mm	mm	mm	Nm
<b>1777027</b>	3	8	2.0-15.0	24	1	11	1
<b>1777025</b>	4	8	2.0-15.0	25	1	11	1
<b>1777024</b>	5	10	0.4 - 4.0	14	1	13	1.8
<b>1777023</b>	5	10	8.0 - 16.0	25	1.3	14	1.8
<b>1777022</b>	5	10	20.0 - 30.0	40	1.3	14	1.8
<b>1777021</b>	6	13	0.4 - 3.0	15	1.3	16	4
<b>1777020</b>	6	13	6.0 - 12.0	25	1.3	16	4
<b>1777005</b>	6	13	12.0 - 25.0	35	1.3	16	4
<b>1777018</b>	8	16	4.0 - 10.0	25	1.3	22	8
<b>1777033</b>	8	18	25.0 - 35.0	50	1.6	20	8
<b>1777016</b>	10	20	25.0 - 35.0	55	1.3	22.5	10
<b>1777015</b>	12	24	35.0 - 45.0	75	1.3	27	15