



Overview

Lead time Usually in Stock

Main

Provided equipment User manual
USB cable

Physical

Height 3.8 cm
Width 12.1 cm
Depth 11.4 cm
Net weight 0.08 kg
Mounting preference No preference
Mounting mode Not rack-mountable

Conformance

Standards EN 55022 class A
EN 55024
ICES-003
Product certifications AS/NZS 3548 (C-Tick) class A[FCC part 15 class A]
GOST[VCCI class A

Environmental

Ambient air temperature for operation 0...45 °C
Operating altitude 0...10000 ft
Relative humidity 0...95 %
Ambient air temperature for storage -5...45 °C
Storage altitude 0.00... 15240.00 m
Storage Relative Humidity 0...95 %

Communications & Management

Authentication Radius

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.1 cm |
| Package 1 Width | 15.9 cm |
| Package 1 Length | 23.5 cm |
| Package 1 Weight | 0.34 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|