

Datasheet

**RS Pro 2 Output Toroidal Transformer, 160VA, 2 x 30V ac**

RS Stock No: **671-9028**



## Product Details

RS Pro 2 output toroidal transformer is a small size and low weight with traditional stacked laminated transformers. It has both primary and secondary windings connected in series or parallel. This transformer has primary voltage rating of 115 V ac, 230 V ac, secondary voltage rating of 2 x 30 V ac and power rating of 160 VA. Toroidal transformer meets EN 61558, IEC 742, UL 506, UL 1411, UL 478 and CE certified.

## Features and Benefits

- Low induced noise (hum)
- Low level of radiated magnetic field
- Flexible leadouts for ease of installation
- 100% electrical and flash testing

**Specifications:**

Diameter	109 mm
Dimensions	109 (dia.) x 46 mm
Height	46 mm
Maximum Operating Frequency	60 Hz
Minimum Operating Frequency	50 Hz
Number of Outputs	2
Power Rating	160 VA
Primary Voltage Rating	230 V ac
Secondary Current	2.667 A
Secondary Voltage Rating	2 x 30 V ac
Termination Type	Copper Conductor
Weight	1.74 kg
Construction	Open
Standards Met	UL 506, IEC 61558 Class II, EN 61558 Class II, VDE0570 Class II, RoHS Compliant

