## Product data sheet Characteristics

# 6225AXXSZS-AC90

Relay, Legacy, solid state, SPST NO, 25A, 24... 280 VAC, 90...280 VAC Uc, SCR AC zero cross, screw terminal



#### Main

Man		
Range	Legacy	i g
Product Type	Solid state relay	
Nominal Output Current	25 A AC	
Network Number of Phases	1 phase	
Mounting Support	Panel	
Output Voltage	24280 V AC	
Control Circuit Voltage	90280 V AC	

### Complementary

o o mpromornary	
Input Impedance	13000 Ohm
Holding Current	120 mA
Input Current Limits	11 mA 120 V AC typical 20 mA 240 V AC
Switch Function	SPST
Contacts Type and Composition	NO
Protection Technology	Current limiter
Tightening Torque	10 lb.in input 20 lb.in output
Connections Terminals	Input screw clamp terminal, 1 Output screw clamp terminals, 1
Screw Type	M3.5 M6
Local Signalling	Input status 1 LED green)
Switching Device	SCR output Zero voltage switching
Maximum Peak Voltage	600 V
Surge Current	250 A 16.6 ms
Must Release Voltage	10 V
Voltage Drop	<1.6 V on-state AC
Power Factor	with maximum load

Insulating Resistance	1 GΩ	
Thermal Resistance	1.02 °C/W	
Maximum I²t for fusing	312 A².s 8.3 ms	
Leakage Current	8 mA at off-state	
DV/Dt	500 V/μs off-state at maximum rated voltage	
Response Time	8.33 ms turn-on) 8.33 ms turn-off)	
Dielectric Strength	4000 V between input and ground 4000 V between output and ground 4000 V between input and output	
Height	1.39 in (35.3 mm)	
Width	1.85 in (47.1 mm)	
Depth	2.30 in (58.4 mm)	
Product Weight	3.05 oz (86.5 g)	
Environment		
Product Certifications	UL CSA CE	
IP Degree of Protection	IP20	
Ambient Air Temperature for Operation	-40176 °F (-4080 °C)	
Ambient Air Temperature for Storage	-40257 °F (-40125 °C)	
Ordering and shipping details		
GTIN	03606480277306	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
	The product must be disposed on European Union markets following specific waste collection and	

never end up in rubbish bins.

## Connections and Wiring Diagrams

