


Datasheet

RS PRO TWIN ROUND BRAIDED SCREEN CABLE 25M

Stock No: 2075341




Technical Specifications:

Conductor	Bare Copper	Mylar tape shielded	-
Cores Number	2C	Braiding	Bare Copper
Size(mm ²)	0.5	Construction(±0.008mm)	16/8/0.10BC
Construction(±0.008mm)	16/0.20	Coverage	≥91%
Stranded Dia.(mm)	0.92	Jacket Material	PVC
Insulation Material	PVC	Jacket Color	Grey (RAL7001)
Insulation Color	Red,Blue	Ave Thickness(mm)	1.00
Ave Thickness(mm)	0.45	Min Thickness(mm)	0.80
Min Thickness(mm)	0.36	Outer Dia(±0.20mm)	6.20
Insulation 1 Dia.(±0.10mm)	1.85		
Filler	Cotton Yarn		
Cabling	Yes		

Features & Benefits:

- **Operating temperature: -20~+60 °C**
- **Conductor resistance(20°C Ω/km): 37max.**
- **Insulation DC Resistance(20°C MΩ*Km): 500min.**
- **Operating voltage: 30 V**

Cross Section drawings



Cable Marking: RS PRO 2 Core×0.5mm²
Screened Cable 30V

Applications:

This multicore microphone cable can be soldered to standard jack and XLR connectors to make custom audio cables that can connect microphones and instruments to mixers or amplifiers. This high-quality audio cable is suitable for:

- Live stages and theatres
- Professional studio setups
- Hobbyist and custom audio setups