

FEATURES

- WATERTIGHT
- INDESTRUCTIBLE
- FOR PROFESSIONAL USE
- PROTECTIVE
- MILITARY GRADE
- WITH PRE-CUBED FOAM
- STACKABLE

RS PRO Flight Cases & Equipment Cases

RS Stock No.: 2537423, 2537424, 2537426, 2537427, 2537428, 2537429, 2537430, 2537431, 2537432, 2537433, 2537434, 2537435, 2537436, 2537437, 2537438, 2537439



Airtight containers, resistant to chemicals, moisture and dust. Resistant to the most extreme temperatures (-33 ° C / + 90 ° C).

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

WATERPROOF CASE IN COPOLYMER POLYPROPYLENE

Indestructible cases recommended for professional use.

REMOVABLE LID WITH SAFETY LOCK

To remove the cover, simply tilt it at 70 ° after releasing the screws on the hinges rear

REINFORCED HINGES WITH ANTI CORROSION METAL PIN

STURDY CLOSURES

SEALING O-RING AND MANUAL PRESSURE RELEASE VALVE

ID REMOVABLE PLATE

ANTI TILT SUPPORTS (in some models)

WITH PRECUBED FOAM INSIDE


SELF OILING FREE RUNNING WHEELS

EASY TO OPEN RELEASE TELESCOPIC HANDLE

TWO MAN LIFT SIDE HANDLES


General Specifications

METRIC MM-KG-C°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	580 mm	L LENGTH	670 mm	WEIGHT EMPTY	9.17 Kg
W WIDTH	440 mm	W WIDTH	510 mm	WEIGHT WITH FOAM	10.40 Kg
D DEPTH	220 mm	D DEPTH	262 mm	WEIGHT WITH CUSTOM FOAM	Kg
LID	60 mm			FOAM VOLUME	56.10 lt
BASE	160 mm			BUOYANCY	36.70 Kg/max
				OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	22 13/16 in	L LENGTH	26 3/8 in	WEIGHT EMPTY	20.21 lbs
W WIDTH	17 5/16 in	W WIDTH	20 1/16 in	WEIGHT WITH FOAM	22.92 lbs
D DEPTH	8 11/16 in	D DEPTH	10 5/16 in	WEIGHT WITH CUSTOM FOAM	lbs
LID	2 3/8 in			FOAM VOLUME	14.79 gal
BASE	6 5/16 in			BUOYANCY	80.90 lbs/max
				OPERATING TEMPERATURE	°F min -27.4 / max +194