

Datasheet

**RS Pro IP67 Black SPDT Rocker Switch, On-On, 0.4 A @
20 V +85°C -30°C 7.11mm 15.75mm**

RS Stock No: **734-6886**



Product Details

RS Pro SPDT rocker switch features gold plated tin contacts with a mechanical life of 30000 make and break cycles. This panel mount switch in black colour, performs on-on operation. It has a glass filled, flame retardant, heat stabilised nylon 6/6 UL94V0 case and bushing material for maximum durability.

Features and Benefits

- SPDT configuration
- Mechanical life of 30000 make and break cycles
- O-Ring seal

**Specifications:**

Actuator Colour	Black
Case Material	Glass Fibre Reinforced Nylon
Contact Configuration	SPDT
Contact Current Rating	0.4 A at 20 V ac/dc
Contact Material	Gold Over Silver Copper Alloy
Contact Resistance	20 mΩ
IP Rating	IP67
Maximum Operating Temperature	+85°C
Mechanical Life	30000 cycles
Minimum Operating Temperature	-30°C
Mounting Type	Panel Mount
Operating Temperature Range	-30 to +85°C
Panel Cut Out Height	7.11 mm
Panel Cut Out Size	7.11 x 15.75 mm
Panel Cut Out Width	15.75 mm
Switch Operation	On-On
Terminal Type	Right Angle PC Pin
Dielectric Strength	1000 V rms
Insulation Resistance	1000 MΩ
Standards Met	RoHS Compliant