

Datasheet

RS PRO Digital Panel Meter Process Monitor

Stock number: 188-3475



PROCESS MONITOR

- 4-digit programmable projection
- Range: $\pm 5 \text{ mA}/\pm 20 \text{ mA}/4\dots 20 \text{ mA}$
 $\pm 2 \text{ V}/\pm 5 \text{ V}/\pm 10 \text{ V}$
- Digital filters
- Size of DIN 51,5 x 29,5 mm
- Power supply 10...30 V DC/24 VAC

188-3475 is a 4-digit process monitor.

The instrument is based on a microcontroller and an A/D converter, which ensures good accuracy and easy operation of the instrument.

The 22 mm cross-section of the circular instrument body allows its convenient mounting into mosaic and signaling panels.

OPERATION

The instrument is set and controlled by two buttons located on its the body.

Standard equipment is the OM Link USB interface, which, when using the control program, allows you to edit and archive all device settings and to update firmware.

All settings are stored in FLASH memory (they hold even after the power is turned off).

STANDARD FUNCTIONS

PROGRAMMABLE PROJECTION

Selection: of input type and measuring range

Setting: manual, optional projection on the display may be set in menu for both limit values of the input signal, e.g. input $0\dots 10 \text{ V} > 0\dots 150,0$

Projection: -999...9999

TECHNICAL DATA

INPUT

Number of inputs	1		
PM Range	optional in configuration menu		
	±5 mA	< 200 mV	Input I
	±20 mA	< 200 mV	Input I
	4...20 mA	< 200 mV	Input I
	±2 V	1 MΩ	Input U
	±5 V	1 MΩ	Input U
	±10 V	1 MΩ	Input U

PROJECTION

Display: -999...9999, single color 7-segm. LED
Digit height: 14 mm
Display color: red
Decimal point: adjustable - in menu
Brightness: adjustable

INSTRUMENT ACCURACY

TK: 50 ppm/°C
Accuracy: ±0,15% of range + 1 digit (for projection -999...1999)
Rate: 0,5...100 measur./s
Overload capacity: 2x; 10x (t < 30 ms)
Watch-dog: reset after 500 ms
Calibration: at 25°C and 40 % r.h.

POWER SUPPLY

Range: 10...30 VDC/24 VAC, ±10 %, PF ≥ 0,4,
 $I_{STP} < 45 \text{ A}/1,1 \text{ ms}$, isolated
Consumption: < 0,2 W/0,2 VA

MECHANIC PROPERTIES

Material: PA66, incombustible UL 94 V-I
Dimensions: 51,5 x 29,5 x 66 mm (w x h x d)
Panel cutout: Ø 22,5 mm

OPERATING CONDITIONS

Connection: connector terminal blocks, section < 1,3 mm²
Stabilization period: within 5 minutes after switch-on
Working temperature: -20°...60°C
Storage temperature: -20°...85°C
Protection: IP65 (front panel only)
El. safety: EN 61010-1, A2
Dielectric strength: 700 VAC per 1 min test between supply and input
Insulation resistance: for pollution degree II, measuring cat. II, power supply > 250 V (PI)
EMC: EN 61326-1

PI - Primary insulation, DI - Double insulation

CONNECTION

