

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Rust Protection 2000 Plus charcoal-grey
Code-Nr. 110120

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Aerosols

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
STOT RE 2	H373	
Aquatic Chronic 3	H412	

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS08

Signal word

Danger

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe vapours/spray.
P273	Avoid release to the environment.
P314	Get medical advice/attention if you feel unwell.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

Naphtha (petroleum), hydrodesulfurized heavy

! Special rules for supplemental label elements for certain mixtures

Contains Fatty acids, tall-oil, reaction products with diethylenetriamine and maleic anhydride, compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers. May produce an allergic reaction.

2.3. Other hazards**Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Compound

! Hazardous ingredients



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Printed

05.08.2019

revision

19.12.2018 (GB) Version 9.2

Rust Protection 2000 Plus charcoal-grey

Hazardous ingredients (continued)

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
100-41-4	202-849-4	ethylbenzene	1 < 10	Flam. Liq. 2, H225 / Acute Tox. 4, H332 / STOT RE 2, H373 (hearing organs) / Asp. Tox. 1, H304
106-97-8	203-448-7	butane	10 - 19,99	Flam. Gas 1, H220 / Press. Gas
123-86-4	204-658-1	n-butyl acetate	< 10	Flam. Liq. 3, H226 / STOT SE 3, H336
1330-20-7	215-535-7	xylene	1 < 10	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Skin Irrit. 2, H315
1314-13-2	215-222-5	zinc oxide	0,25 < 1	Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
74-98-6	200-827-9	propane	10 - 19,99	Flam. Gas 1, H220 / Press. Gas, H280
64742-82-1	265-185-4	Naphtha (petroleum), hydrodesulfurized heavy	2,5 < 10	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / STOT RE 1, H372
64742-95-6	918-668-5	Hydrocarbons, C9,arom. hydrotreater (-)	2,5 < 10	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335, H336 / Aquatic Chronic 2, H411
61790-69-0	263-160-2	Fettsäuren, Talloel-, Reaktionsprodukte mit Diethylentriamin	0,1 < 0,25	Acute Tox. 4, H302 / Skin Corr. 1B, H314 / STOT RE 2, H373 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
1262797-52-3		Fatty acids, tall-oil, reaction products with diethylenetriamine compds. with polyethylene glycol hydrogen maleate C9-11-alkyl Fatty acids, tall-oil, reaction products with diethylenetriamine compd. with polyethylene glycol hydrogen maleate C9-11-alkyl ether	0,25 < 1	Skin Sens. 1, H317 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410

REACH

CAS No	Name	REACH registration number
100-41-4	ethylbenzene	01-2119489370-35
106-97-8	butane	01-2119474691-32
123-86-4	n-butyl acetate	01-2119485493-29
1330-20-7	xylene	01-2119488216-32
1314-13-2	zinc oxide	01-2119463881-32
74-98-6	propane	01-2119486944-21
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	01-2119458049-33
64742-95-6	Hydrocarbons, C9,arom. hydrotreater (-)	01-2119455851-35
61790-69-0	Fettsäuren, Talloel-, Reaktionsprodukte mit Diethylentriamin	01-2119411392-51

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.



In case of ingestion

Do not induce vomiting.

If swallowed seek medical advice immediately and show the doctor packing or label.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

sand

Unsuitable extinguishing media

water

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Vapours are heavier than air and will spread on the ground.

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not seep away runed out product into ground or body of water.



6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale aerosols

Ensure sufficient ventilation.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Store at +5 till +25 °C.

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
100-41-4	Ethylbenzene	8 hours	441	100	EH40/2005
		Short-term	552	125	
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	
100-41-4	Ethylbenzol (CH)	MAK, 8 hours	220	50	Niere, Leber, Methode: NIOSH
		Short-term	220	50	
123-86-4	n-Butyl acetate	8 hours	724	150	
		Short-term	966	200	

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
100-41-4	ethylbenzene	8 hours	442	100	skin
		Short-term	884	200	
1330-20-7	xylene, mixed isomers, pure	8 hours	221	50	skin
		Short-term	442	100	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
100-41-4	ethylbenzene	77 mg/m3	DNEL long-term inhalative (systemic)	
123-86-4	n-butyl acetate	2 mg/kg	DNEL short-term oral (acute)	
		480 mg/m3	DNEL long-term inhalative (systemic)	
		11 mg/kg	DNEL long-term dermal (systemic)	
		960 mg/m3	DNEL acute inhalative (systemic)	
		600 mg/m3	DNEL acute inhalative (local)	
		11 mg/kg	DNEL acute dermal, short-term (systemic)	
1314-13-2	zinc oxide	300 mg/m3	DNEL long-term inhalative (local)	
		83 mg/kg	DNEL long-term dermal (systemic)	
		5 mg/m3	DNEL long-term inhalative (systemic)	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	330 mg/m3	DNEL long-term inhalative (systemic)	
		44 mg/kg	DNEL long-term dermal (systemic)	
64742-95-6	Hydrocarbons, C9,arom. hydrotreater (-)	150 mg/m3	DNEL long-term inhalative (systemic)	
		25 mg/kg bw/day	DNEL long-term dermal (systemic)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 19.12.2018 (GB) Version 9.2

Rust Protection 2000 Plus charcoal-grey

PNEC

CAS No	Substance name	Value	Code	Remark
123-86-4	n-butyl acetate	0,018 mg/l	PNEC aquatic, marine water	
		0,981 mg/kg	PNEC sediment, freshwater	
		0,18 mg/l	PNEC aquatic, freshwater	
1314-13-2	zinc oxide	0,0206 mg/l	PNEC aquatic, freshwater	
		56,5 mg/kg	PNEC sediment, marine water	
		117,8 mg/kg	PNEC sediment, freshwater	
		0,0061 mg/l	PNEC aquatic, marine water	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	20 mg/l	PNEC sewage treatment plant (STP)	
		0,0749 mg/l	PNEC aquatic, freshwater	

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

! Hand protection

Gloves (solvent-resistant)

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

safety goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

aerosol

Colour

grey

Odour

solvent-like

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 19.12.2018 (GB) Version 9.2

Rust Protection 2000 Plus charcoal-grey

	Value	Temperature	at	Method	Remark
melting point	not applicable				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	not determined				
Vapour density	not determined				
Solubility in water					immiscible
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Oxidising properties	No information available.				
Explosive properties	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
9.2. Other information	Vapours are heavier than air.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Gases/vapours, harmful

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	8700 mg/kg	rat		Xylol
LD50 acute dermal	> 2000 mg/kg		estimate	ATE
LC50 acute inhalation	> 20 mg/l (4 h)		estimate	ATE
Skin irritation	irritant			
Eye irritation	irritant			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

May cause damage to organs, if longer exposed.



Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Vapours may cause dizziness, headaches and tiredness

Risk of strong health injuries in case of long-term exposition.

Irritates respiratory tract.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

16 05 04*

Name of waste

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

Transport as limited quantities according to 3.4 IMDG Code is possible.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 55,7 %**VOC value** 511 g/L**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 9.1

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 19.12.2018 (GB) Version 9.2

Rust Protection 2000 Plus charcoal-grey

H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335,	-?-
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.