

## FEATURES

- Waterproof thermostat housed in a polycarbonate box
- Switches heating loads or cooling devices
- Screwdriver adjustable temperature range
- Current of 10 A
- SPDT (single pole double throw) switch configuration
- Voltage of 240 V AC
- Temperature range of -5°C to +25°C

## RS PRO Thermostats, -5 → +25 °C

RS Stock No.: 440-7972



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

When you need a waterproof thermostat to maintain the temperature of your home or workplace, turn to this RS PRO thermostat. It's housed inside an impermeable, polycarbonate box, so it can be used in areas where water ingress is a problem. That could include the area around a water pump or inside a damp property.

The thermostat can be used to adjust the temperature of both heating and air conditioning systems. For added safety, the thermostat itself is IP65 rated, meaning it's resistant to dust, as well as water sprayed from a low-pressure nozzle. You can easily adjust the thermostat's temperature setting, which ranges from -5°C to +25°C, using a screwdriver.

## General Specifications

<b>Product Type</b>	Waterproof thermostat
<b>Switch Configuration</b>	SPDT (single pole double throw)
<b>Temperature Range</b>	-5°C to +25°C
<b>Maximum Temperature</b>	+25°C
<b>Minimum Temperature</b>	-5°C
<b>Colour</b>	White
<b>Additional Features</b>	Switches heating loads or cooling devices
<b>Applications</b>	Warehouses, Car Parks, Walkways, Construction areas, Parks and gardens, Home security

## Electrical Specifications

<b>Supply Voltage</b>	240VAC
<b>Contact Rating</b>	10A
<b>Operation</b>	Turn

## Protection Category

<b>IP Rating</b>	IP65
------------------	------

## Approvals

<b>Compliance/Certifications</b>	RoHS Compliant, ANSI/ESD S20.20:2014 and BS EN 61340-5-1:2007, EU Directives 2011/65/EU and 2015/863
----------------------------------	--





