

Product data sheet

Characteristics

33682

MN delay unit, MasterPact NT/NW,
ComPact NS, adjustable time delay 0.5s/3s,
200/250VDC, 200/250VAC 50/60Hz, spare part



Main

| | |
|------------------------------|--|
| Device short name | MN delay unit |
| Product or component type | Time delay relay |
| Device application | Control |
| Range compatibility | Masterpact (MasterPact NT) Masterpact (MasterPact NW) ComPact (ComPact NSX) ComPact (ComPact NS630b...1600) ComPact (ComPact NS1600b...3200) PowerPact (PowerPact Multistandard) ComPact (ComPact NSXm) ComPact (ComPact NSX DC) Masterpact (MasterPact NW UL 489) Masterpact (MasterPact NT UL 489) Masterpact (MasterPact NW DC) |
| Voltage release type | Undervoltage release |
| [Uc] control circuit voltage | 200...250 V AC 50/60 Hz 200...250 V DC |

Complementary

| | |
|------------------------------------|---|
| Impulse duration | 200 ms |
| Time delay range | 0.5...3 s |
| Threshold tripping voltage | 0.35...0.7 Un open 0.85 Un close |
| Supply holding power | 4.5 VA |
| Supply inrush power | 200 VA |
| Mounting mode | External mounting |
| Response time | 0.5 s 1 s 1.5 s 3 s |
| Accessory / separate part category | Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.0 cm |
| Package 1 Width | 8.0 cm |
| Package 1 Length | 9.0 cm |
| Package 1 Weight | 166.0 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 36 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 6.463 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| PVC free | Yes |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|