

Datasheet

Product Name: UL1429 22AWG
Product Discription: UL1429 22AWG
Specification No.:
Customer's Name:

					Customer's Name.				
Description					Construction				
Rated \	/oltage:		150V		Conductor	Stranded Tinned Co	pper		
Rated 1	emperature:		80℃		Size(AWG)	22			
Referer	nce Standard:	UL7	58,UL1581		Construction(±0.008mm)	7/0.254			
Cross Section					Stranded Dia.(mm)Ref.	0.76			
					Insulation Material	ation Material XLPVC			
					Insulation Color	ulation Color ANY COLOR			
					Ave Thickness(mm)	0.23			
					Insulation Dia.(±0.06mm)	1.28			
Marking					Remark:				
					8775355 Red	8775364 Blue	e 8775377 Grey	8775386 Violet	
E148000 ऒ AWM STYLE 1429 22AWG 80℃ 150V VW-1					8775358 Black	8775367 Whit	te 8775370 Yellow		
C 匆 AWM I A 80°C 150V FT1-FLF- PC10 LTK					8775351 Brown	8775361 Gre	en 8775373 Orange		
					Characteristics		cs	Customer Approve	
Applications					Test Item		Standard Value		
For Internal Wiring of Appliances or Electronic Equipment					Test Material		XLPVC(ROHS)		
					Insulation DC resistance(MΩ*km)		10		
					Vol. Tesr(AC.V.60S) (V)		2000	Seal & Stamp	
					Flammability Test		VW-1		
Revisions					Max.DC Resistance(20℃ Ω/km)		59.4(MAX)		
Version	Description	otion Drawn by Approved by Date							
0	New document issu	e Lisa	Jason	18/05/2015					
								Signature:	
								Date:	

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.