Shrouded Pin Header, 1.25mm, SMD

multicomp PRO

RoHS

Compliant



Specifications

Current Rating : 1A AC/DCVoltage Rating : 125V AC/DCContact Resistance : $20m\Omega Max$. Insulation Resistance : $100M\Omega Min$.


Withstanding Resistance : 250V AC for one minute

Operating Temperature Range : -40°C to +85°C

Material and Finish

Insulator : High Temp. Plastic (UL94V-0)

Contact : Copper Alloy Plated : Tin Plated



P.C.B LATYOUT SURFACE MOUNTING

Dimension Table

Part Number	Contacts	Α	В	С
MC34437	2	1.25	7.25	4.25
MC34413	3	2.5	8.5	5.5
MC34439	4	3.75	9.75	6.75
MC34415	5	5	11	8
MC34441	6	6.25	12.25	9.25
MC34831	7	7.5	13.5	10.5
MC34443	8	8.75	14.75	11.75
MC34421	15	17.5	23.5	20.5

Dimensions: Millimetres

Part Number Table

Description	Part Number
Shrouded Straight Pin Header, 2 Pos, 1.25mm, SMD	MC34437
Shrouded Straight Pin Header, 3 Pos, 1.25mm, SMD	MC34413
Shrouded Straight Pin Header, 4 Pos, 1.25mm, SMD	MC34439
Shrouded Straight Pin Header, 5 Pos, 1.25mm, SMD	MC34415
Shrouded Straight Pin Header, 6 Pos, 1.25mm, SMD	MC34441
Shrouded Straight Pin Header, 7 Pos, 1.25mm, SMD	MC34831
Shrouded Straight Pin Header, 8 Pos, 1.25mm, SMD	MC34443
Shrouded Straight Pin Header, 15 Pos, 1.25mm, SMD	MC34421

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

