

Surface Mount Schottky Barrier Rectifiers

multicomp PRO



Features

- Low profile package
- Ideal for automated placement
- Ultrafast reverse recovery time
- Low power losses, high efficiency
- Low forward voltage drop
- High surge capability
- High temperature soldering: 260°C/10 seconds at terminals

**RoHS
Compliant**

Mechanical Data





Case : JEDEC SMB molded plastic body over passivated chip
 Terminals : Solder plated, solderable per J-STD-002B and JESD22-B102D
 Polarity : Laser band denotes cathode end
 Reverse Voltage : 20 Volts
 Forward Current : 1 Ampere

Maximum Ratings, Thermal Characteristics and Electrical Characteristics

(T_A = 25 °C unless otherwise noted)

Characteristics	Symbol	Values	Unit
Max. Repetitive Peak Reverse Voltage	V _{RRM}	20	V
Max. RMS Voltage	V _{RMS}	14	
Max. DC Blocking Voltage	V _{DC}	20	
Maximum average forward rectified current	I _{F(AV)}	1	A
Peak forward surge current 8.3 ms single half sine wave superimposed on rated load	I _{FSM}	40	
Maximum instantaneous forward voltage at 1A	V _F	0.5	V
Max. DC Reverse Current at Rated DC Blocking Voltage	I _R	T _A = 25°C 0.5	mA
		T _A = 125°C 5	
Thermal resistance from junction to Lead	R _{θJL}	30	°C/W
Operating junction and storage temperature range	T _J , T _{STG}	-65 to +125	°C

Rating and Characteristic Curves



Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro


multicomp PRO

Surface Mount Schottky Barrier Rectifiers

multicomp PRO

Diagram

DO-214AA (SMB)



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
Schottky Rectifier, 20V, 1A, DO-214AA (SMB), 2 Pins	SS12B

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO