



母线加工工具系列 three-in-one busbar processors

功能说明 Function

- ▲分离式液压冲孔器适用于L、H平板钢，铜排与铝排冲孔。
- ▲底处设计有平座、平稳不易倒晃。
- ▲单孔式回油，模具采用高碳钨合金钢不易破损。
- ▲Suitable for punching holes on "L" and "H" shape iron plates, copper & aluminum busbars.
- ▲Flat pedestal to provide steadiness in operation.
- ▲Punch dies made of high carbon tungsten steel and not easy to wear off.

技术参数 Technical parameters

| 型号 Model | 吨位 Tonnage (T) | 配置模具 Bending formers (In) | 最大厚度 Max. thickness (mm) | | 喉深 Throat th (mm) | 重量 Weight (kg) | 体积 Volume (mm) |
|-------------|-------------------|--|--------------------------|---------------------|----------------------|-------------------|-------------------|
| | | | 铁板 Iron sheet | 铜排 copper busbar | | | |
| HHM-60 | 31 | φ3/8" (11.1), φ1/2" (14.3), φ5/8" (17.5), φ3/4" (20.6) | 6mm | 10mm | 70 | 21.5 | 400X250X150 |
| HHM-70 | 35 | φ3/8" (11.1), φ1/2" (14.3), φ5/8" (17.5), φ3/4" (20.6) | 8mm | 12mm | 110 | 37.5 | 330X200X390 |
| HHM-80 | 50 | φ16(5/8"), φ18(3/4"), φ22(7/8"), φ25(1") | 14mm | 16mm | 115 | 52 | 370X225X400 |

功能说明 Function

- ▲弯曲铜排或铝排弯曲角度90° 正确、不损伤到铜的材质。
- ▲HHM-150W是可掀式、当弯曲长条铜排时，N形或L形可以将卡栓拆出、则可整排拿出不受阻碍。
- ▲设计上有角度规定90°、45° 指示、避免过度。
- ▲Designed for bending cast copper and aluminum busbars.
- ▲Easy to carry and simple to operate.
- ▲Make easy bends and free of damage to the material.

技术参数 Technical parameters

| 型号 Model | 出力 Output (T) | 宽度 Breadth (mm) | 最大厚度 Max. Thickness (mm) | 重量 Weight (kg) | 体积 Volume (mm) |
|-------------|------------------|--------------------|-----------------------------|-------------------|-------------------|
| HHM-125W | 25 | 40-125 | 6-12.5 | 42.5 | 380X270X150 |
| HHM-150W | 16 | 150 | 10 | 19.5 | 400X190X290 |
| HHM-200W | 16 | 200 | 12 | 26.5 | 280X210X380 |