

Product Specification

MT-1217



Model No.	MT-1217
Digits	3 5/6digits, 5999 counts
DCV	600mV/6V /60V/600V±(0.5%+4d) 1000V ±(1%+6d)
ACV	600mV±(1%+10d), 6V /60V/600V±(0.8%+6d), 750V ±(1%+10d), True RMS
DCA	600uA/6000uA/60mA/600mA, ±(1%+10d), 10A±(1.2%+10d)
ACA	600uA/6000uA/60mA/600mA, ±(1.5%+10d), 10A±(2.5%+15d), True RMS
Frequency response	40Hz~1000Hz
Resistance	600Ω±(0.8%+5d), 6K/60K/600K/6M±(0.8%+4d),

	60MΩ ±(1.2%+10d)
Capacitance	9.999nF ±(5 %+35) 9.999nF~~999.9uF ±(3.5%+8) 999.9uF~6mF ±(3.5%+35)
Frequenct	10~20MHz±(1%+10d)
Temperature	-20°C~1000°C, <400°C±(1.0%+5d) ≥400°C±(1.5%+15d)
	-4°F~ 1832°F, < 752°F±(1.0%+5d), ≥ 752°F±(1.5%+15d)
NCV detection	Y
Buzzer	Y
Diode test	Y
Triode test	Y
Hz/% Test	Y
Relative value	Y
Data hold	Y
Auto power off	Y
LED backlight	Y
Safety standard	CE,CAT III 1000V
Power source	9V(6F22*1)

