



Main

| | |
|---------------------------|----------------|
| Range | PratiKa |
| Product or component type | Socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|-------------------------------------|---|
| Mounting mode | Wall-mounted |
| Plug, socket, control station shape | Angled |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel |
| Connections - terminals | Captive screws, completely loosened |
| Cable cross section | 2.5...10 mm ² |
| Cable outer diameter | 11.5...21 mm |
| Cable entry | Cable gland |
| Thread type | Pg 21 |
| Net weight | 0.557 kg |
| Base dimension | 106 x 130 mm |
| Height | 194 mm |
| Width | 106 mm |
| Depth | 154 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|---------------------------------------|---|
| Standards | EN 60309-1 EN 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Ambient air temperature for operation | 35 °C (86400 s) |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.7 cm |
| Package 1 Width | 15.2 cm |
| Package 1 Length | 19.2 cm |
| Package 1 Weight | 498.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 12.6 cm |
| Package 2 Width | 26.2 cm |
| Package 2 Length | 26.8 cm |
| Package 2 Weight | 1.156 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 6 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 3.955 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|