

FEATURES

- Fits standard rectangular cutout.
- Front or rear mounting through the panel.
- Various hole mounting options.
- No soldering or punch termination. Use standard cable for each connector style.
- Low rear profile.
- 90° or right angle rear cable entry.

RS PRO HDMI Right Angle Feedthrough Connectors

RS Stock No.: **2576723, 2576724, 2576725, 2576726**



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the

leading brands without paying a premium price.

Product Description

HDMI Right angle feedthrough connector. A feedthrough, data connector for electrical instrumentation. Used for developing custom I/O configurations for wall plates, rack panels, etc.

Common cabling can be used for front and rear connections. No soldering and no punch terminations - just use the standard cable for that particular connector style.

A low rear profile accommodates the tightest behind-the-panel spaces.

Please note: Functionality is affected by cable quality, length and cable wiring configuration.

General Specifications

Gender	Female
Number of Contacts	19
Size	See drwg
Contact Material	Brass
Contact Plating	Gold plating
Body Orientation	Right angle
Termination Method	Feed through
Housing Material	Insert: ABS UL94-V2 Frame: Diecast, Nickel or Black plated
Frame Colour	Metal
Maximum Operating Temperature	Max +60°C
Minimum Operating Temperature	Min -10°C

Mechanical Specifications

Mounting Hole	CSK hole
Frame Style	Metal Slim type

Approvals

Compliance/Certifications	REACH, RoHS
---------------------------	-------------

Similar Products

Parameters	2576724	2576725	2576726
Brand	RS RPO	RS RPO	RS RPO
Gender	Female	Female	Female
Number of Contacts	19	19	19
Size	See drwg	See drwg	See drwg
Contact Material	Brass	Brass	Brass
Contact Plating	Gold plating	Gold plating	Gold plating
Body Orientation	Right angle	Right angle	Right angle
Termination Method	Feed through	Feed through	Feed through
Maximum Operating Temperature	Max +60°C	Max +60°C	Max +60°C
Minimum Operating Temperature	Min -10°C	Min -10°C	Min -10°C
Mounting Hole	M3	CSK	M3
Frame Style	Metal Slim	Metal Slim	Metal Slim
Frame Colour	Metal	Black	Black

HDMI Feedthrough Connectors

