

LUPROMAX METALWORKING FLUIDS SERIES

PRODUCT BROCHURE

Version Release 2007.7.1



LUPROMAX LUBRICANT RANGE

- Metalworking Fluids
- · Greases Mineral, Silicone, Synthetic
- · Gear Oil Additives
- · Open Gear Lubricants
- Pulling Lubricants

- · Engine Oil Additives
- · Fuel Oil Additives
- · Penetrating Oil Additives
- Wirerope Lubricants
- · Aerosol Lubricants

PRODUCT MODEL

LUPROMAX

PRODUCT CATEROGY

LUPROMAX Metalworking Fluids Series

PRODUCT NAME

LUPROMAX-MF-TAP PREMIUM

HIGH QUALITY TAPPING FLUID

PRODUCT DESCRIPTION

LUPROMAX-MF-TAP PREMIUM is a high quality tapping fluid, specially formulated for dimensional accuracy tapping, and good surface finish of component. LUPROMAX-MF-TAP PREMIUM eliminates pulling and seizing, reduces tapping torque and extends tool life. It can be used for all types of machining operations including tapping, reaming, threading, drilling. turning, broaching and milling.

FEATURES & BENEFITS

 LOWERS TEMPERATURE FAST Improves Tap Performance in any material. LUPROMAX-MF- TAP PREMIUM effectively transfers heat away from the metal surface through liquid vapourization.

Magna

Headquarters & Far East
Office:
Magna International Pte Ltd
Blk 9005, Tampines Street 93,
#02-242 Tampines Industrial Park A,
Singapore 528839
Tel (65) 6788-1228
Fax (65) 6785-1497
Email
magnaintl@pacific.net.sg
Website
http://www.magnachem.com.sg

North America Office: No. 15 Bowman Avenue Matheson, Ontario POK 1N0 Canada Tel 705-273-3353 Fax 705-273-3352 Email magna@ntl.sympatico.ca LUPROMAX-MF-TAP www.lupromax.com



FEATURES & BENEFITS

- SUPERIOR RUST INHIBITION
 Protects equipment and work piece from corrosion.
- GOOD LUBRICATING PROPERTIES Increases tool life and improves dimensional accuracy. EXCLUSIVE MISER SPOUT

Permits drop by drop pin-point accuracy application, prevents excessive wastage and keeps the hand of the operator away from the danger cutting tool.

- WETTING ABILITY
 With effective wetting agents allow fast, effective penetration into cutting zone.
- MULTI METALS
 It's effective on all materials, ferrous and non-ferrous metals.

T.L.V.

• 350 P.P.M.

COLOUR

• Green

DIRECTIONS FOR USE

LUPROMAX-MF-TAP PREMIUM can be used neat, simply spray LUPROMAX-MF-TAP PREMIUM on the work piece through a hand dispenser of the machine pump and experience the optimum tap performance of LUPROMAX-MF TAP PREMIUM.

TYPICAL PROPERTIES

FORM

Light Fluid

ODOUR
• Pleasant

· i icasai

pH • 7

SPECIFIC GRAVITY

• 1.42

Please contact our distributor or reseller for more information:

Headquarters & Far East Office:
Magna International Pte Ltd
Blk 9005, Tampines Street 93,
#02-242 Tampines Industrial Park A,
Singapore 528839.
Tel (65) 6788-1228
Fax (65) 6785-1497
Email magnaintl@pacific.net.sg
Website http://www.magnachem.com.sg

North America Office: No. 15 Bowman Avenue Matheson, Ontario P0K 1N0 Canada Tel 705-273-3353 Fax 705-273-3352 Email magna@ntl.sympatico.ca

Magna International Pte Ltd.

Website: http://www.magnachem.com.sg

For more information about how Lupromax works, please request for HOW LUPROMAX WORKS brochure from any LUPROMAX representative.