

## Datasheet

# RS PRO GREY 4 CORE STANDARD MICROPHONE CABLE,50m

Stock No: 2075323




### Technical Specifications:

Conductor	Tinned Copper	Cotton Paper	Yes
Cores Number	4C	Braiding Shield	Tinned Copper
Size(mm <sup>2</sup> )	0.15	Construction(±0.008mm)	16/3/0.15TC
Construction(±0.008mm)	14/0.12	Jacket Material	PVC
Stranded Dia.(mm)	0.51	Jacket Color	Grey(RAL7001)
Insulation Material	PVC	Ave Thickness(mm)	0.60
Insulation Color	RD,WH,BU,GN	Min Thickness(mm)	0.48
Ave Thickness(mm)	0.39	Outer Dia(±0.15mm)	4.70
Min Thickness(mm)	0.31		
Insulation Dia.(±0.10mm)	1.30		
Drain Wire	-		
Cabling	Yes		

## Features & Benefits:

- **Operating temperature: -20~+80 °C**
- **Conductor resistance(20°C Ω/km): 122max.**
- **Insulation DC Resistance(20°C MΩ\*Km): 200min.**
- **Operating voltage: 1000 V**

## Cross Section drawings



**Cable Marking:** RS PRO 4 Core×0.15mm<sup>2</sup>  
Microphone Cable 1000V

## Applications:

This multicore microphone cable can be soldered to standard jack and XLR connectors to make custom audio cables that can connect microphones and instruments to mixers or amplifiers. This high-quality audio cable is suitable for:

- Live stages and theatres
- Professional studio setups
- Hobbyist and custom audio setups